



NOTES:

1. CURB RETURN RADIUS DIMENSIONS AT INTERSECTIONS MAY VARY DEPENDING ON MEDIAN WIDTH AND WILL BE APPROVED ON A CASE BY CASE BASIS.
2. SUBDRAINS ARE REQUIRED ON ALL MEDIANS. (TO BE TIED INTO STORM DRAINAGE SYSTEM.) REFER TO SUBDRAIN STANDARD DETAIL 312.1.
3. MEDIAN PLANTINGS SHALL NOT OBSTRUCT INTERSECTION SIGHT DISTANCE REQUIREMENTS.
4. A TEN (10) FOOT WIDE MEDIAN IS REQUIRED FOR SMALL MATURING TREES. A TWENTY (20) FOOT WIDE MEDIAN IS REQUIRED FOR LARGE MATURING TREES.
5. BIKE LANE TO BE STRIPED.
6. SEE SECTION II. B. FOR ADDITIONAL DESIGN CRITERIA.

KEY

- (R) 2'-6" STD. CURB AND GUTTER
- (S) 4" CONCRETE SIDEWALK
- (T) 1'-6" MEDIAN CURB AND GUTTER

NOT TO SCALE

REV. DATE	10/01/15
STD. NO.	210.2